

**LRCV AD 2.1 AERODROME LOCATION INDICATOR AND NAME****LRCV - CRAIOVA / Craiova****LRCV AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

1	ARP co-ordinates and site at AD	441905N 0235319E Runway center.
2	Direction and distance from city	90°, 7 km from Craiova
3	Elevation/Reference temperature	626 FT / 30.1°C
4	Geoid undulation at AD ELEV PSN	134 FT
5	MAG VAR/ Annual rate of change	4°E (2010) / -
6	AD Administration, address, telephone, telefax, e-mail, AFS, website	Aeroportul Internațional Craiova Str. Calea București Nr. 325, cod. 200785, Craiova, Jud. Dolj Tel: +40-(0)251-412564 Tel/Fax: +40-(0)251-416860; +40-(0)251-411112 AFS: LRCVRYD e-mail: mircea@aeroportcraiova.ro, m_aeroportcv@yahoo.com web: www.aeroportcraiova.ro
7	Types of traffic permitted (IFR/VFR)	IFR/VFR
8	Remarks	NIL

**LRCV AD 2.3 OPERATIONAL HOURS**

1	AD Administration	H24
2	Customs and immigration	H24
3	Health and sanitation	As AD Administration
4	AIS Briefing Office	H24, see GEN 3.1-5
5	ATS Reporting Office (ARO)	H24, see ENR 1.10-2
6	MET Briefing Office	H24
7	ATS	H24
8	Fuelling	As AD Administration
9	Handling	As AD Administration
10	Security	H24
11	De-icing	As AD Administration
12	Remarks	NIL

**LRCV AD 2.4 HANDLING SERVICES AND FACILITIES**

1	Cargo-handling facilities	4 electric truck, 6 trailers, 2 GPU 115v 400hz and 28.5v, 1 air starter unit, 1 air conditioner, 3 self propelled telescopic passenger stairs, 2 airport bus, 2 airport passenger/crew minibuses, 2 luggage belts, 1 self propeller potable water car, 1 self propeller lavatory service car, 1 ambulance car, 1 ambulift car, 2 push-back truck (1 truck with tow bar for B737/A320/A321 and 1 truck towbarless), 1 forklift.
2	Fuel/Oil types	JET A1 / NIL
3	Fuelling facilities/capacity	1 refueling truck of 4000 l, refueling rate 180 l/min, 1 refueling truck of 32000 l, refueling rate 800 l/min, storage 70000 l.
4	De-icing facilities	1 de-icing unit Global with fluid Type I (capacity 3800 l) and Type II (capacity 1100 l) and 1 unit Mallgan with fluid Type I (capacity 6400 l) and Type II (capacity 2100 l), 1 heater with hot air for engines.
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	Fueling operations for charter flights must be announced 2h before.

**LRCV AD 2.5 PASSENGER FACILITIES**

1	<i>Hotels</i>	Hotels in the city.
2	<i>Restaurants</i>	1 restaurant, 1 snack-bar, 1 bar on the AD.
3	<i>Transportation</i>	Buses, taxis from the AD, Rent-a-car office at the AD.
4	<i>Medical facilities</i>	First aid at AD, doctor, ambulance, hospitals in the city.
5	<i>Bank and Post Office</i>	Bank, Exchange office and money transfer, A.T.M. on the AD.
6	<i>Tourist Office</i>	At AD.
7	<i>Remarks</i>	Nil.

**LRCV AD 2.6 RESCUE AND FIRE FIGHTING SERVICES**

1	<i>AD category for fire fighting</i>	Within AD HR: CAT 7
2	<i>Rescue equipment</i>	1 rescue equipment type HOLMATRO, 1 electric steel cutter, 1 steel strapping cutter, 1 electrical generator.
3	<i>Capability for removal of disabled aircraft</i>	Nil
4	<i>Remarks</i>	Nil

**LRCV AD 2.7 SEASONAL AVAILABILITY - CLEARING**

1	<i>Types of clearing equipment</i>	2 snowblower, 1 equipment with brush and blade, 1 autospreader de-icing.
2	<i>Clearance priorities</i>	1. RWY 09/27 2. TWY B 3. APRON
3	<i>Remarks</i>	Information on snow clearance published from November-April in NOTAM (SNOWTAM). See also the snow plan in section AD 1.2

**LRCV AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA**

1	<i>Apron designation, surface and strength</i>	Surface: Asphalt / Concrete Strength: 30/R/D/W/T / 52/R/D/W/T
2	<i>Taxiway designation, width, surface and strength</i>	TWY B Width: 18 M Surface: Asphalt Strength: 46/F/C/W/T
3	<i>ACL location and elevation</i>	Location: At apron Elevation: 630 FT
4	<i>VOR checkpoints</i>	Nil
5	<i>INS checkpoints</i>	See AD 2.9-22 Aircraft Parking/Docking Chart  INS 01 44°18'48.04"N 23°52'44.32"E INS 02 44°18'49.04"N 23°52'44.29"E INS 03 44°18'47.96"N 23°52'39.58"E INS 04 44°18'49.47"N 23°52'39.54"E INS 05 44°18'51.04"N 23°52'39.51"E INS 06 44°18'52.66"N 23°52'39.46"E INS 07A 44°18'53.82"N 23°52'39.52"E INS 07 44°18'54.72"N 23°52'39.49"E INS 08A 44°18'56.35"N 23°52'39.45"E INS 08 44°18'56.57"N 23°52'39.44"E
6	<i>Remarks</i>	Aircraft Stand Manoeuvring Guidance Lights at Stand no.: 01, 02, 03, 04, 05, 06, 07A, 07, 08A, 08.

**LRCV AD 2.9 SURFACE MOVEMENT GUIDANCE AND  
CONTROL SYSTEM AND MARKINGS**

1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	Taxiing guidance signs at intersection with TWY B and holding position. Guide line at Apron.
2	RWY and TWY markings	RWY: - markings: color white: designation, THR, TDZ, aiming point, centre line, side stripes; - lights: runway edge lights, THR lights, runway end lights, wing bar lights, runway centre line lights, TDZ lights; TWY B: - markings: color yellow: centreline, RWY holding position, enhanced centreline, runway designation marking; - lights: centre line lights, taxiway edge lights, stop bar lights, runway guard lights.
3	Stop bars	Red stop bars at RWY holding position.
4	Remarks	Nil

**LRCV AD 2.10 AERODROME OBSTACLES**

In approach / TKOF areas			In circling area and at AD		Remarks
1			2		3
RWY/Area affected	Obstacle type Elevation Markings/LGT	Co-ordinates	Obstacle type Elevation Markings/LGT	Co-ordinates	
a	b	c	a	b	
27/APCH 09/TKOF	Power line 220M/722FT	441923.27N 0235731.52E	Water tower 226.8M/744FT	441835.30N 0235232.48E	
	Antenna 207.3M/680FT	441901.46N 0235704.24E	Antenna 234.9M/771FT	442108.71N 0235309.71E	
09/APCH 27/TKOF	Antenna 226.8M/744FT LGT	441848.40N 0235213.49E	TV Antenna 288M/945FT	442206.14N 0234927.93E	
	Antenna 287.9M/945FT LGT	442025.79N 0235053.09E	Antenna 216.7M/711FT	441839.37N 0235254.29E	
			Chimney 275M/902FT	442042.95N 0234852.84E	

**LRCV AD 2.11 METEOROLOGICAL INFORMATION PROVIDED**

1	Associated MET Office	CRAIOVA
2	Hours of service MET Office outside hours	As ATS
3	Office responsible for TAF preparation Periods of validity Interval of issuance	LROM 9 HR 3 HR, during aerodrome operational hours
4	Type of landing forecast Interval of issuance	Nil -
5	Briefing / consultation provided	Self-briefing; briefing/consultation on request (see row 8)
6	Flight documentation  Language(s) used	Charts, tabular form, abbreviated plain language text Romanian, English
7	Charts and other information available for briefing or consultation	SWC, W/T Charts, SIGMET, METAR, TAF.
8	Supplementary equipment available for providing information	Tel/FAX: +40-(0)251-410631
9	ATS units provided with information	CRAIOVA TWR
10	Additional information (limitation of service, etc.)	Nil

**LRCV AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS**

<i>Designations RWY NR</i>	<i>TRUE BRG</i>	<i>Dimensions of RWY (M)</i>	<i>Strength (PCN) and surface of RWY and SWY</i>	<i>THR coordinates RWY end coordinates THR geoid undulation</i>	<i>THR elevation and Highest elevation of TDZ of precision APP RWY</i>
1	2	3	4	5	6
09	088.93°	2500 x 45	46/F/C/W/T Asphalt	441904.57N 0235222.58E 441906.07N 0235415.11E GUND 134 FT	THR 626 FT
27	268.95°	2500 x 45	46/F/C/W/T Asphalt	441906.07N 0235414.85E 441904.57N 0235222.31E GUND 134 FT	THR 614.4 FT TDZ 614.6 FT
<i>Slope of RWY-SWY</i>	<i>SWY dimensions (M)</i>	<i>CWY dimensions (M)</i>	<i>Strip dimensions (M)</i>	<i>OFZ</i>	<i>Remarks</i>
7	8	9	10	11	12
-0.16%	Nil	300 x 210	2620 x 300	Nil	RESA 240x90M
+0.16%	Nil	500 x 210	2620 x 300	Nil	RESA 240x90M

**LRCV AD 2.13 DECLARED DISTANCES**

<i>RWY designator</i>	<i>TORA (M)</i>	<i>TODA (M)</i>	<i>ASDA (M)</i>	<i>LDA (M)</i>	<i>Remarks</i>
1	2	3	4	5	6
09	2500	2800	2500	2494	Nil
27	2500	3000	2500	2494	Nil

**REDUCED DECLARED DISTANCES**

<i>RWY designator</i>	<i>TORA (M)</i>	<i>TODA (M)</i>	<i>ASDA (M)</i>	<i>Remarks</i>
1	2	3	4	5
09 "TWY B"	2000	2300	2000	Nil

**LRCV AD 2.14 APPROACH AND RWY LIGHTING**

<i>RWY Designator</i>	<i>APCH LGT type LEN INTST</i>	<i>THR LGT colour WBAR</i>	<i>VASIS (MEHT) PAPI</i>	<i>TDZ, LGT LEN</i>	<i>RWY Centre Line LGT Length, spacing, colour, INTST</i>	<i>RWY edge LGT LEN, spacing, colour, INTST</i>	<i>RWY End LGT colour WBAR</i>	<i>SWY LGT LEN (M) colour</i>	<i>Remarks</i>
1	2	3	4	5	6	7	8	9	10
09	SALS 420M LIH	Green WBAR LIH	PAPI 3° (47 FT)	Nil	1600M,15M, White, LIH 600M, 15M, Red/White, LIH 300M, 15M, Red, LIH	1900M,60M, White, LIH 600M,60M, Yellow, LIH	Red LIH	Nil	Nil
27	CAT II/III 900M LIH	Green WBAR LIH	PAPI 3° (56 FT)	900M White 30M	1600M,15M, White, LIH 600M, 15M, Red/White, LIH 300M, 15M, Red, LIH	1900M,60M, White, LIH 600M,60M, Yellow, LIH	Red LIH	Nil	Nil

**LRCV AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY**

1	<i>ABN / IBN location, characteristics and hours of operation</i>	Nil
2	<i>LDI location and LGT Anemometer location and LGT</i>	Nil
3	<i>TWY edge and centre line lighting</i>	TWY edge blue omnidirectional,50M, TWY "B", centre line: yellow/ green exit taxiway centre line, green entry taxiway centre line.
4	<i>Secondary power supply/switch-over time</i>	Secondary power supply to all lighting on RWY's and TWY's, max, switch-overtime 1s.
5	<i>Remarks</i>	Nil

**LRCV AD 2.16 HELICOPTER LANDING AREA**

1	Co-ordinates TLOF or THR of FATO Geoid undulation	Nil Nil
2	TLOF and/or FATO elevation M/FT	Nil
3	TLOF and FATO area dimensions, surface, strength, marking	Nil
4	True and MAG BRG of FATO	Nil
5	Declared distance available	Nil
6	APP and FATO lighting	Nil
7	Remarks	Nil

**LRCV AD 2.17 ATS AIRSPACE**

1	Designation and lateral limits	CRAIOVA CTR A circle, radius 20 NM centred at 441905N 0235319E (ARP)
2	Vertical limits	SFC to 5500 FT STD
3	Airspace classification	C
4	ATS unit call sign Language(s)	Craiova Tower English, Romanian
5	Transition altitude	3 000 FT AMSL
6	Hours of applicability	As ATS
7	Remarks	Nil

**LRCV AD 2.18 ATS COMMUNICATION FACILITIES**

Service designation	Call sign	Channel/ Frequency	SATVOICE	Logon address	Hours of operation	Remarks
1	2	3	4	5	6	7
APP/TWR	Craiova Tower	129.530 124.300 MHz ALTN 121.500 MHz EMERG	Nil	Nil	As ATS	Exempted 8.33 kHz State aircraft.

**LRCV AD 2.19 RADIO NAVIGATION AND LANDING AIDS**

Type of aid, MAG VAR CAT of ILS/MLS (For VOR/ILS/MLS give declination)	ID	Frequency	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
DVOR/DME (4°E/2010)	CRV	110.200 MHz (CH 39X)	H24	441907.0N 0235521.9E	600 FT	086° MAG / 0.80 NM from THR 27 Coverage 100 NM (assumed)
LOC 27 (4°E/2010) ILS CAT I	ICV	108.700 MHz	H24	441904.4N 0235207.9E		Front course angle 4.34°
GP 27	-	330.500 MHz	H24	441909.8N 0235401.4E		GP angle 3.0° ILS RDH 54 FT
DME	ICV	CH 24X	H24	441909.9N 0235401.3E	600 FT	

**LRCV AD 2.20 LOCAL AERODROME REGULATIONS**

- Nil -

**LRCV AD 2.21 NOISE ABATEMENT PROCEDURES**

See AD 1.1-3

**LRCV AD 2.22 FLIGHT PROCEDURES**

- Nil -

**LRCV AD 2.23 ADDITIONAL INFORMATION**

- Nil -

**LRCV AD 2.24 CHARTS RELATED TO THE AERODROME**

Aerodrome Chart - ICAO .....	AD 2.9-20
Aerodrome Parking/Docking Chart - ICAO .....	AD 2.9-22
Aerodrome Obstacle Chart – ICAO – Type A .....	AD 2.9-25
Instrument Approach Charts - ICAO	
RWY 27 ILS CAT A / B .....	AD 2.9-51
RWY 27 ILS CAT C / D .....	AD 2.9-52
RWY 27 VOR CAT A / B .....	AD 2.9-81
RWY 27 VOR CAT C / D .....	AD 2.9-82
RWY 09 VOR/DME .....	AD 2.9-83
RWY 27 NDB – CAT A / B .....	AD 2.9-91
RWY 27 NDB – CAT C / D .....	AD 2.9-92