



TABULAR DESCRIPTION

RNP RWY35R – Instrument Approach Procedure

Serial Number	Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	VPA/ TCH	Navigation Specification
010	IF	INLER	-	-			-	+4000 (1)	AT 190	-	RNAV 1
020	TF	TODKU	-	349 (352.3)		4.0	-	+3000	180	-	RNAV 1
030	TF	MC802	-	346 (349.1)		4.0	-	+3000	170	-	RNP APCH
040	TF	RWY35R	Y	346 (349.0)		7.1	-	@748(2)	-	3.0/ 17.5	RNP APCH
050	CF	MC803	Y	346 (349.0)	3	-	-	+1450	200	-	RNP APCH
060	CF	MC804	-	107 (110.0)	3	-	R	+3500	200	-	RNAV 1
070	TF	SRN	-	107 (109.8)		-	-	+4000	-	-	RNAV 1

(1) +3000FT ATC discretion

(2) THR Altitude plus TCH; for MA transition the value is according to the minima LNAV or LNAV/VNAV

HOLDING IAF - RNAV 1

Path Terminator	Waypoint Identifier	Inbound Course °M (°T)	Leg Distance (NM) (1)	Timing(min.)/ Waypoint Distance (NM) (2)	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Specification
HM	INLER	356 (359.0)	3.5	1.0/ -	R	+4000	-	190	3	RNAV1

(1) RNAV system with holding functionality

(2) RNAV system without holding functionality

HOLDING MISSED APPROACH - CONVENTIONAL

Path Terminator	Waypoint (FIX)	Inbound Course °M (°T)	Navaid	Outbound leg	Turn Direction	Minimum Altitude (FT)	Maximum Altitude (FL)	Speed Limit (kt)	Magnetic Variation (°)	Navigation Performance
HM	SRN VOR NDB/DME	123 (126.0)	SRN VOR NDB/DME	-	R	+4000	-	210	3	Conventional

WAYPOINT LIST

Waypoint Identifier	Coordinates
MC802	45°30'00.08" N 008°46'09.78" E
MC803	45°39'47.19" N 008°43'27.87" E
MC804	45°41'22.61" N 008°50'59.08" E

SBAS FAS DATA BLOCK LIMC RNP RWY35R

Parameters		Values
Operation Type		0
SBAS Provider		1
Airport Identifier		LIMC
Runway		35
Runway Direction		1
Approach Performance Designator		0
Route Indicator		
Reference Path Data Selector		0
Reference Path Identifier		E35A
LTP/FTP Latitude		453656.7015N
LTP/FTP Longitude		0084414.9860E
LTP/FTP Ellipsoidal Height (metres)		255.8
FPAP Latitude		453901.3310N
Delta FPAP Latitude (seconds)		124.6295
FPAP Longitude		0084340.5460E
Delta FPAP Longitude (seconds)		-34.4400
Threshold Crossing Height		17.50
TCH Units Selector		1
Glidepath Angle (degrees)		3.00
Course Width (metres)		105.00
Length Offset (metres)		0
HAL (metres)		40.0
VAL (metres)		50.0

Output Data	
Data Block	10 03 0D 09 0C 63 00 00 01 35 33 05 FB 7E 93 13 14 EE BF 03 FE 1D AB CD 03 F0 F2 FE 5E 81 2C 01 64 00 C8 FA E2 6F 15 D3
Calculated CRC Value	E26F15D3

Required Additional Data (not CRC wrapped)	
These additional data are not required for CRC calculation, but they need to be provided to datahouses for procedure coding in ARINC 424 records.	
Parameters	Values
ICAO Code	LI
LTP/FTP Orthometric Height (metres)	210.6
FPAP Orthometric Height (metres)	234.1

Intenzionalmente bianca

Intentionally left blank