

AIRAC effective date 27 JAN 2022 (A13/21)

NOISE ABATEMENT PROCEDURES RWY 35R

SID DESCRIPTION RWY 35R

REMARK

SID MMP 6S, SRN 6S, TELVA 6S only for ACFT cat. A/B/C.

WARNING

There are close-in obstacles penetrating OIS 2.5% but they were not considered for the published procedure design gradient (see ICAO Obstacle Charts and NOTAM in force).

DOGUB 6T

REMARK

Minimum climb gradient 7.41% (450 ft/NM) until passing 3000 ft.

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	346 (349.0)	-	-	-	1162	-	RNAV1
CF	MC604	Y	356 (359.0)	3	-	-	2300	-	RNAV1
DF	MC613	-	-	-	-	L	5000	- 220	RNAV1
TF	DOGUB	-	235 (238.1)	-	4.3	-	6000	-	RNAV1

MMP 6L

REMARK

Minimum climb gradient 7.41% (450 ft/NM) until passing 3000 ft.

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	346 (349.0)	-	-		1162	-	RNAV1
CF	MC604	Y	356 (359.0)	3	-		2300		RNAV1
DF	MC608	-	-	-	-	R	4000	- 220	RNAV1
TF	MC603	Y	106 (108.9)	-	2.0	-	-	-	RNAV1
CF	MMP	-	266 (268.6)	3	-	R	6000	- 230	RNAV1

MMP 6M

REMARK

Minimum climb gradient 7.41% (450 ft/NM) until passing 3000 ft.

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	346 (349.0)	-	-	-	1162	-	RNAV1
CA	-	-	356 (359.0)	-	-	-	1300	-	RNAV1
CF	MC611	-	356 (359.0)	3	-	-	-	-	RNAV1
TF	MC602	-	069 (072.2)	-	3.1	-	3000	- 200	RNAV1
CF	MC607	Y	036 (039.2)	3	1.5	-	3500	-	RNAV1
CF	MMP	-	266 (268.6)	3	-	R	6000	- 220	RNAV1

MMP 6S**REMARK**

Minimum climb gradient 7.41% (450 ft/NM) until passing 4000 ft, then 5.76% (350 ft/NM).

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	346 (349.0)	-	-	-	1162	-	RNAV1
CA	-	-	356 (359.0)	-	-	-	1300	-	RNAV1
CF	MC607	Y	036 (039.2)	3	-	-	3500	- 200	RNAV1
CF	MMP	-	266 (268.6)	3	-	R	6000	- 220	RNAV1

SRN 6L**REMARK**

Minimum climb gradient 7.41% (450 ft/NM) until passing 3000 ft.

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	346 (349.0)	-	-	-	1162	-	RNAV1
CF	MC604	Y	356 (359.0)	3	-	-	2300	-	RNAV1
DF	MC608	-	-	-	-	R	4000	- 220	RNAV1
TF	MC603	-	106 (108.9)	-	2.0	-	-	-	RNAV1
TF	SRN	-	123 (125.8)	-	9.3	-	6000	- 230	RNAV1

SRN 6M**REMARK**

Minimum climb gradient 7.41% (450 ft/NM) until passing 3000 ft.

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	346 (349.0)	-	-	-	1162	-	RNAV1
CA	-	-	356 (359.0)	-	-	-	1300	-	RNAV1
CF	MC611	-	356 (359.0)	-	-	-	-	-	RNAV1
TF	MC602	-	069 (072.2)	-	3.1	-	3000	- 200	RNAV1
TF	MC603	-	036 (039.0)	-	3.2	-	-	-	RNAV1
TF	SRN	-	123 (125.8)	-	9.3	-	6000	- 220	RNAV1

SRN 6S**REMARK**

Minimum climb gradient 7.41% (450 ft/NM) until passing 3000 ft.

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	346 (349.0)	-	-	-	1162	-	RNAV1
CA	-	-	356 (359.0)	-	-	-	1300	-	RNAV1
CF	MC607	-	036 (039.2)	3	-	-	3500	- 200	RNAV1
TF	MC603	-	036 (038.9)	-	1.6	-	-	-	RNAV1
TF	SRN	-	123 (125.8)	-	9.3	-	6000	- 220	RNAV1

TELVA 6L (ATC discretion)**REMARK**

Minimum climb gradient 7.41% (450 ft/NM) until passing 3000 ft.

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	346 (349.0)	-	-	-	1162	-	RNAV1
CF	MC604	Y	356 (359.0)	3	-	-	2300	-	RNAV1
DF	MC608	-	-	-	-	R	4000	220	RNAV1
TF	MC603	Y	106 (108.9)	-	2.0	-	-	-	RNAV1
CF	MC612	-	173 (175.5)	3	-	-	TRL	- 230	RNAV1
TF	TELVA	-	173 (175.5)	-	5.9	-	FL100	-	RNAV1

TELVA 6M (ATC discretion)**REMARK**

Minimum climb gradient 7.41% (450 ft/NM) until passing 3000 ft.

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	346 (349.0)	-	-	-	1162	-	RNAV1
CA	-	-	356 (359.0)	-	-	-	1300	-	RNAV1
CF	MC611	-	356 (359.0)	3	-	-	-	-	RNAV1
TF	MC602	-	069 (072.2)	-	3.1	-	3000	- 200	RNAV1
CF	MC607	Y	036 (039.2)	3	1.5	-	3500	-	RNAV1
CF	MC612	-	173 (175.5)	3	-	R	TRL	- 220	RNAV1
TF	TELVA	-	173 (175.5)	-	5.9	-	FL100	-	RNAV1

TELVA 6S (ATC discretion)**REMARK**

Minimum climb gradient 7.41% (450 ft/NM) until passing 4000 ft, then 5.76% (350 ft/NM).

Path Terminator	Waypoint Identifier	Fly Over	Course °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (ft)	Speed Limit (kt)	Navigation Specification
CA	-	-	346 (349.0)	-	-	-	1162	-	RNAV1
CA	-	-	356 (359.0)	-	-	-	1300	-	RNAV1
CF	MC607	Y	036 (039.2)	3	1.5	-	3500	-	RNAV1
CF	MC612	-	173 (175.5)	3	-	R	TRL	- 220	RNAV1
TF	TELVA	-	173 (175.5)	-	5.9	-	FL100	-	RNAV1

USE OF AERODROME BY AIRCRAFT CHAPTER 2 ANNEX 16 ICAO

Aircraft Chapter 2 Annex 16 ICAO cannot use Milano/Malpensa airport, except for emergency.

WAYPOINT LIST

Waypoint Identifier	Coordinates
MC602	45°41'41.23" N 008°47'50.28" E
MC603	45°44'08.61" N 008°50'40.95" E
MC604	45°42'32.03" N 008°43'34.15" E
MC607	45°42'51.59" N 008°49'12.24" E
MC608	45°44'48.75" N 008°47'53.80" E
MC611	45°40'44.30" N 008°43'36.77" E
MC612	45°35'47.48" N 008°54'30.60" E
MC613	45°42'55.09" N 008°36'12.45" E